

XHTML Cheat Sheet v. 1.03

		BLOCK ELEMENTS		deprecated elements	
%attrs	address	information on author	%attrs	applet	
%coreattrs	blockquote	long quotation	%attrs, cite	center	
%i18n	div	generic container (block)	%attrs, align*	dir	
%events	dl	definition list	%attrs, compact*	menu	
%coreattrs	fieldset	form control group	%attrs	basefont	
id	form	interactive form	%attrs, action , method, enctype, accept, name*, onsubmit, onreset, accept-charset, target*	font	
class	h1-h6	six levels of headings	%attrs, align*	isindex	
style	hr	horizontal rule	%attrs, align*, size*, width*, noshade*	s	
title	noframes*	alternate content for non frame-based rendering	%attrs	strike	
%i18n	noscript	content when scripts disabled	%attrs	u	
xml:lang	ol	ordered list	%attrs, type*, start*, compact*	entities	
lang	p	paragraph	%attrs, align*	" "	
dir	pre	preformatted text	%attrs, width*	& &	
%events	ul	unordered list	%attrs, type*, compact*	< <	
onclick	INLINE ELEMENTS			> >	
ondblclick	a	anchor (or link)	%attrs, charset, type, name, rel, rev, href, hreflang, target*, shape, coords, %focus	' '	
onmousedown	abbr	abbreviation	%attrs	(space) 	
onmouseup	acronym	acronym (UNO, NATO,...)	%attrs	i ¡	
onmouseover	b	bold text	%attrs	¢ ¢	
onmousemove	bdo	I18N BiDi over-ride	%coreattrs, %events, xml:lang, lang, dir	£ £	
onmouseout	big	large font	%attrs	¤ ¤	
onkeypress	br	forced line break	%coreattrs, clear*	¥ ¥	
onkeydown	button	push button	%attrs, name, value, type, <i>disabled</i> , %focus	¡ ¦	
onkeyup	cite	citation or reference	%attrs	§ §	
%focus	code	computer code	%attrs	¨ ¨	
accesskey	dfn	definition	%attrs	© ©	
tabindex	em	emphasis	%attrs	ª ª	
onfocus	i	italic text	%attrs	« «	
onblur	iframe*	inline subwindow	%coreattrs, lndesc, name, src, frameborder, marginwidth, marginheight, scrolling, align*, height, width	¬ ¬	
input types	img	embedded image	%attrs, src , alt , longdesc, name, height, width, usemap, <i>ismap</i> , align*, border*, hspace*, vspace*	- (cond.) ­	
text	input	form control	%attrs, type, name, value, <i>checked</i> , <i>disabled</i> , <i>readonly</i> , size, maxlength, src, alt, <i>ismap</i> , usemap, onselect, onchange, accept, %focus, align*	® ®	
password	kbd	text to be entered by the user	%attrs	™ &smacr;	
checkbox	label	form field label text	%attrs, for, accesskey, onfocus, onblur	° °	
radio	map	client-side image map	%i18n, %events, id , class, style, title, name	± ±	
submit	object	generic embedded object	%attrs, <i>declare</i> , classid, codebase, data, type, codetype, archive, standby, height, width, usemap, name, tabindex, align*, border*, hspace*, vspace*	¹ ¹	
image	q	short inline quotation	%attrs, cite	² ²	
reset	samp	sample output from scripts	%attrs	³ ³	
button	select	option selector	%attrs, name, size, <i>multiple</i> , <i>disabled</i> , tabindex, onfocus, onblur, onchange	' ´	
hidden					µ µ
file					¶ ¶
link types (rel, rev)					· ·
alternate					¸ ¸
stylesheet					º º
start					» »
next					¼ ¼
prev					½ ½
contents					¾ ¾
index					¿ ¿
glossary					À À
copyright					Á Á
chapter					Â Â
section					Ã Ã
subsection					Ä Ä
appendix					Å Å
help					Æ Æ
bookmark					Ç Ç
media descriptors					È È
screen					É É
tty					Ê Ê
tv					Ë Ë
projection					Ì Ì
handheld					Í Í
print					Î Î
braille					Ï Ï
aural					Ð Ð
all					Ñ Ñ
					Ò Ò
					Ó Ó
					Ô Ô
					Õ Õ
					Ö Ö

